



Leica TP1020

Automatic tissue processor for the histology laboratory

Living up to Life

Leica
MICROSYSTEMS

Reliable Technology, Maximum Specimen Safety

Leica sets new standards in many fields of application with technically innovative instruments for specimen preparation. The Leica TP1020 is an automatic tissue processor that perfectly combines approved technology with modern, user-friendly design. Gentle specimen processing and maximum safety for tissue at all stages of the processing run, robust engineering design based on innovative precision mechanics in conjunction with a modern user interface – these are the convincing features of the Leica TP1020. Easy to program, this instrument offers the user utmost flexibility to suit the individual requirements of any laboratory.

Reduced exposure to hazardous fumes

The instrument variation with fume control system offers two options for removing solution fumes:



- The use of two different activated carbon filters (for formalin and alcohol/xylene) frees the exhaust air from the solution fumes and releases the cleansed air into the ambient atmosphere.
- An exhaust air tube directs the solution fumes to an outlet.

The efficiency of the system is further enhanced by a two-part plexiglass fume containment shield surrounding the reagent container platform.



Tissue infiltration under vacuum

Vacuum can be applied to any of the stations both in manual and automatic operation. The advantage: substantially improved infiltration of tissue in a shorter time. Instruments with the vacuum feature are equipped with anodized aluminum containers.



Maximum safety for the tissue

The tissue specimens are protected from drying out even during a power failure since the tissue baskets are automatically immersed in a station. The program is resumed where interrupted once mains power is restored. After a long-term power failure, the wax will be liquefied.

If the programmed infiltration time for any of the stations is exceeded a warning message is displayed indicating the station number and the time in excess of program.



User-friendly, easy-to-use control panel

The buttons of the control panel are arranged in functional groups. The easy-to-read LCD indicates the station parameters such as number of tissue baskets, vacuum function and remaining infiltration time, real time, start time (delayed start), overall duration and end of run time. Each of the nine programs can be run with immediate or delayed start.

Practical details

The specimen throughput can be doubled by using a second tissue basket for improved productivity in routine and research laboratories. The tissue basket is moved up and down in the liquid at three-second intervals to ensure thorough and even mixing of the reagents and optimum infiltration of the tissue. Sealing rings on the container lids reduce solution loss and therefore also emission into the ambient atmosphere to a minimum. All reagent stations are easily accessible because the instrument can be



rotated nearly immediately and without difficulty by using the integrated and adjustable rollers.

Four configurations are available: basic instrument; base instrument with vacuum; base instrument with fume control system; and base instrument with vacuum and fume control.



Leica TP1020 with vacuum and fume control

Wide range of accessories:

- Glass beakers with beaker carriers
- Anodized aluminum container with beaker carriers
- Teflon coated wax bath



- Three-part tissue basket with lid (for organized loading of cassettes)
- Standard tissue baskets
- Basket removal device with drip tray



Leica TP1020 – Outstanding Product Features

- Carousel type with 12 stations
- Configurations: – Basic instrument
 - Vacuum function
 - Fume control system
 - Vacuum function with fume control system
- Option: two basket loading
- Tissue baskets made of metal with varying capacities of up to 100 cassettes
- Ergonomic control panel with foil-protected keyboard and LCD
- Infiltration time separately programmable for each station
- Delayed start function up to 9 days
- Possibility of interrupting an automatic process for reloading or removing cassettes for special applications before the end of a run
- Easy editing and changing of programs, even during a processing run
- Audible alarms, error messages and warning codes
- Advanced safety concept
- Wide range of accessories

Leica TP1020 – Technical Specifications

Electrical specifications:

Nominal voltage: 100 / 120 / 230 / 240 V AC ±10%

Nominal frequency: 50 / 60 Hz

Dimensions:

Carousel lid: 820 mm Ø

Height: 595 – 780 mm

Diameter of rollers: 610 mm

Weight:

Dry weight (including accessories): 60 kg

Wax baths:

Number: 2 (3 optional)

Capacity: 1.8 l

Temperature range: 45 °C – 65 °C

Excess temperature cutout: 75 °C ± 4 °C

Reagent containers:

Number: 10 (9)

Capacity: 1.8 l

Standard tissue basket:

Number: 1 (2 optional)

Capacity: max. 100 cassettes

Programs:

Number: 9, freely selectable

Programmable infiltration time

per station: 99 h 59 min

Delayed start: 9 days

Drain time: 60 s

Vacuum device (depending on the configuration):

Pressure difference: max. 500 hPa (approx. 0.5 bar)

Up-to-date development, production and quality control procedures certified under DIN EN ISO 9001 ensure highest quality and reliability.

Active worldwide

Australia:	North Ryde	Tel. +61 2 8870 3500	Fax +61 2 9878 1055
Austria:	Vienna	Tel. +43 1 486 80 50 0	Fax +43 1 486 80 50 30
Belgium:	Groot Bijgaarden	Tel. +32 2 790 98 50	Fax +32 2 790 98 68
Canada:	Richmond Hill/Ontario	Tel. +1 905 762 2000	Fax +1 905 762 8937
Denmark:	Herlev	Tel. +45 4454 0101	Fax +45 4454 0111
France:	Nanterre Cedex	Tel. +33 811 000 664	Fax +33 1 56 05 23 23
Germany:	Wetzlar	Tel. +49 64 41 29 40 00	Fax +49 64 41 29 41 55
Italy:	Milan	Tel. +39 02 574 861	Fax +39 02 574 03392
Japan:	Tokyo	Tel. +81 3 5421 2800	Fax +81 3 5421 2896
Korea:	Seoul	Tel. +82 2 514 65 43	Fax +82 2 514 65 48
Netherlands:	Rijswijk	Tel. +31 70 4132 100	Fax +31 70 4132 109
People's Rep. of China:	Hong Kong	Tel. +852 2564 6699	Fax +852 2564 4163
Portugal:	Lisbon	Tel. +351 21 388 9112	Fax +351 21 385 4668
Singapore		Tel. +65 6779 7823	Fax +65 6773 0628
Spain:	Barcelona	Tel. +34 93 494 95 30	Fax +34 93 494 95 32
Sweden:	Kista	Tel. +46 8 625 45 45	Fax +46 8 625 45 10
Switzerland:	Heerbrugg	Tel. +41 71 726 34 34	Fax +41 71 726 34 44
United Kingdom:	Milton Keynes	Tel. +44 1908 246 246	Fax +44 1908 609 992
USA:	Bannockburn/Illinois	Tel. +1 847 405 0123	Fax +1 847 405 0164

and representatives in more than 100 countries

www.leica-microsystems.com

Leica
MICROSYSTEMS